



# Test Report: RSP-750-27

---

750W Single Output Power Supply

## ■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Control Function Test

Component Stress Test

## ■ SAFETY & E.M.C. TEST

Safety Test

E.M.C. Test

## ■ RELIABILITY TEST

ENVIRONMENT TEST

## ■ ESIGN VERIFY TEST

### OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1 : 150 mVp-p (Max)	I/P : 230VAC O/P : FULL LOAD Ta : 25°C	V1 : 67 mVp-p (Max)	P
2	OUTPUT VOLTAGE ADJUST RANGE	CH1 : 24V ~ 30V	I/P : 230 VAC I/P : 115 VAC O/P : MIN LOAD Ta : 25°C	22.448 V ~ 31.469 V / 230 VAC 22.451 V ~ 31.469 V / 115 VAC	P
3	OUTPUT VOLTAGE TOLERANCE	V1 : 1% ~ -1% (Max)	I/P : 100VAC / 264 VAC O/P : FULL / MIN LOAD Ta : 25°C	V1 : 0.05 % ~ -0.05 %	P
4	LINE REGULATION	V1 : 0.5% ~ -0.5% (Max)	I/P : 100VAC ~ 264 VAC O/P : FULL LOAD Ta : 25°C	V1 : 0.03 % ~ -0.03 %	P
5	LOAD REGULATION	V1 : 0.5% ~ -0.5% (Max)	I/P : 230 VAC O/P : FULL ~ MIN LOAD Ta : 25°C	V1 : 0.05 % ~ -0.05 %	P
6	SET UP TIME	230VAC : 1000 ms (Max) 115VAC : 1000 ms (Max)	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 171 ms 115VAC/ 340 ms	P
7	RISE TIME	230VAC : 50 ms (Max) 115VAC : 50 ms (Max)	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 36 ms 115VAC/ 35 ms	P
8	HOLD UP TIME	230VAC : 16 ms (TYP) 115VAC : 16 ms (TYP)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 26 ms 115VAC/ 27 ms	P
9	OVER/UNDERSHOOT TEST	< ±5%	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	TEST : <5 %	P
10	DYNAMIC LOAD	V1 : 2700 mVp-p	I/P : 230 VAC (1).O/P : FULL /Min LOAD 90%DUTY/ 1KHZ (2).O/P : FULL /Min LOAD 90%DUTY/ 3KHZ (3).O/P : FULL /Min LOAD 90%DUTY/ 5KHZ (4).O/P : FULL /Min LOAD 50%DUTY/ 120HZ Ta : 25°C	(1)700 mVp-p (2)659 mVp-p (3)603 mVp-p (4)1.09 Vp-p	P



## INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	90VAC~264 VAC	I/P : TESTING O/P : FULL LOAD Ta : 25°C	73 V~264V	P
			I/P : LOW-LINE-3V=87 V HIGH-LINE+15%=300 V O/P : FULL/MIN LOAD ON : 30 Sec . OFF : 30 Sec 10MIN ( AC POWER ON/OFF NO DAMAGE )	TEST : OK	
2	INPUT FREQUENCY RANGE	47HZ ~63 HZ NO DAMAGE OSC	I/P : 100VAC ~ 264 VAC O/P : FULL~MIN LOAD Ta : 25°C	TEST : OK	P
3	POWER FACTOR	0.97 / 230 VAC(TYP)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	PF= 0.988 / 230 VAC	P
		0.98 / 115 VAC(TYP)		PF= 0.998 / 115 VAC	
4	EFFICIENCY	90.5% (TYP)	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	90.876 %	P
5	INPUT CURRENT	230V/ 3.9 A (TYP)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	I = 3.659 A/ 230 VAC	P
		115V/ 8.9 A (TYP)		I = 7.546 A/ 115 VAC	
6	INRUSH CURRENT	230V/ 40 A (TYP)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	I = 38 A/ 230 VAC	P
		115V/ 25 A(TYP) COLD START		I = 18 A/ 115 VAC	
7	LEAKAGE CURRENT	< 2 mA / 240 VAC	I/P : 264 VAC O/P : Min LOAD Ta : 25°C	L-FG : 0.8 mA N-FG : 0.68 mA	P

## PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	105 ~ 125 %	I/P : 230 VAC I/P : 115 VAC O/P : TESTING Ta : 25°C	115.258% / 230 VAC 115.258% / 115 VAC Constant Current Limiting	P
2	OVER VOLTAGE PROTECTION	CH1 : 31V ~ 36.5 V	I/P : 230 VAC I/P : 115 VAC O/P : MIN LOAD Ta : 25°C	33.457V / 230 VAC 33.504V / 115 VAC Shut down Re- power ON	P
3	OVER TEMPERATURE PROTECTION	SPEC : TSW1 : 80 ± 5°C O.T.P. TSW2 : 85 ± 5°C O.T.P. NO DAMAGE	I/P : 230 VAC O/P : FULL LOAD	O.T.P. Active Shut down o/p voltage , recovers automatically after temperature goes down	P
4	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P : 264 VAC O/P : FULL LOAD Ta : 25°C	NO DAMAGE CONSTANT CURRENT LIMITING	P

## CONTROL FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT																		
1	REMOTE ON/OFF CONTROL	Power on : short between on/off (pin13) & 12V-AUX(pin14) on CN50 Power off : open between on/off (pin13) & 12V-AUX(pin14) on CN50	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	TEST : OK	P																		
2	DC OK SIGNAL	The TTL signal out, PSU turn on = 0 ~ 1V PSU turn off = 3.3 ~ 5.6V	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	0 V 4.915 V	P																		
3	OUTPUT VOLTAGE PROGRAMMABLE(PV)		I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	<table border="1"> <thead> <tr> <th>ADJ V</th> <th>2V</th> <th>3V</th> <th>4V</th> <th>5V</th> <th>5.5V</th> </tr> </thead> <tbody> <tr> <td>SPEC</td> <td>40%</td> <td>60%</td> <td>80%</td> <td>100%</td> <td>110%</td> </tr> <tr> <td>TEST</td> <td>41.5%</td> <td>61.4%</td> <td>81.8%</td> <td>102%</td> <td>111.9%</td> </tr> </tbody> </table>	ADJ V	2V	3V	4V	5V	5.5V	SPEC	40%	60%	80%	100%	110%	TEST	41.5%	61.4%	81.8%	102%	111.9%	P
ADJ V	2V	3V	4V	5V	5.5V																		
SPEC	40%	60%	80%	100%	110%																		
TEST	41.5%	61.4%	81.8%	102%	111.9%																		
4	OUTPUT CURRENT PROGRAMMABLE(PC)		I/P : 230 VAC O/P : 0%~110 LOAD Ta : 25°C	<table border="1"> <thead> <tr> <th>ADJ V</th> <th>2V</th> <th>3V</th> <th>4V</th> <th>5V</th> <th>5.5V</th> </tr> </thead> <tbody> <tr> <td>SPEC</td> <td>40%</td> <td>60%</td> <td>80%</td> <td>100%</td> <td>110%</td> </tr> <tr> <td>TEST</td> <td>38.3%</td> <td>58.3%</td> <td>80.4%</td> <td>101.59%</td> <td>112.39%</td> </tr> </tbody> </table>	ADJ V	2V	3V	4V	5V	5.5V	SPEC	40%	60%	80%	100%	110%	TEST	38.3%	58.3%	80.4%	101.59%	112.39%	P
ADJ V	2V	3V	4V	5V	5.5V																		
SPEC	40%	60%	80%	100%	110%																		
TEST	38.3%	58.3%	80.4%	101.59%	112.39%																		
5	REMOTE SENSE	>0.5V	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	>0.54	P																		
6	FAN SPEED	FAN Voltage : 0% LOAD 7~9V 100%LOAD 11.5~12.5V	I/P : 230 VAC O/P : 0%~100%LOAD Ta : 25°C	O/P : 0% LOAD FAN Voltage : 7.968V O/P : 100%LOAD FAN Voltage : 12.078V	P																		
7	AUXILIARY POWER	12V@ 0.1 A(±10%)	I/P : 230 VAC O/P : 0%~100%LOAD Ta : 25°C	O/P : 0% LOAD 12.528 V O/P : 100%LOAD 12.295 V	P																		

## COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor ( D to S) or (C to E) Peak Voltage	Q905 Rated : STP7N95K3 7A/950V	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25°C	(1) 824 V (2) 816 V (3) 820 V	P
2	Diode Peak Voltage	D101 Rated : V30100S 30A/100V  Q201 Rated : YA868C15RSC 30A/150V	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on (2)Output Short (3)Full load continue  O/P : (1)Full Load Turn on (2)Output Short (3)Full load continue Ta : 25°C	(1) 53.6 V (2) 55.6 V (3) 51.2 V  (1) 99.6 V (2) 98.4 V (3) 98 V	P
3	Input Capacitor Voltage	C5 Rated : 330u/400V 105°C 30*30 HU	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C	(1) 384 V (2) 382 V (3) 396 V	P
4	Control IC Voltage Test	U901 Rated : UCC28220D 8V~14V	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C	(1) 12.3 V (2) 12.1 V (3) 12 V	P
5	Power Transistor ( D to S) or (C to E) Peak Voltage	Q 2 Rated : FCP22N60N 22A/600V	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25°C	(1) 428 V (2) 400 V (3) 418 V	P

## ■ SAFETY & E.M.C. TEST

### SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P : 3 KVAC/min I/P-FG : 2KVAC/min O/P-FG : 0.5 KVAC/min	I/P-O/P : 3.6 KVAC/min I/P-FG : 2.4 KVAC/min O/P-FG : 0.6 KVAC/min Ta : 25°C	I/P-O/P : 9. mA I/P-FG : 8.3 mA O/P-FG : 6.7 mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P : 500VDC>100MΩ I/P-FG : 500VDC>100MΩ O/P-FG : 500VDC>100MΩ	I/P-O/P : 500 VDC I/P-FG : 500 VDC O/P-FG : 500 VDC Ta : 25°C /70%RH	I/P-O/P : 15.5 GΩ I/P-FG : 12.2 GΩ O/P-FG : 13.2 GΩ NO DAMAGE	P
3	GROUNDING CONTINUITY	FG(PE) TO CHASSIS OR TRACE < 100 mΩ	40 A / 2min Ta : 25°C / 70%RH	10 mΩ	P

### E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	HARMONIC	EN61000-3-2 CLASS A CLASS D	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	PASS	P
2	CONDUCTION	EN55022 CLASS B	I/P : 230 VAC (50HZ) O/P : FULL/50% LOAD Ta : 25°C	PASS Test by certified Lab	P
3	RADIATION	EN55022 CLASS B	I/P : 230 VAC (50HZ) O/P : FULL LOAD Ta : 25°C	PASS Test by certified Lab	P
4	E.S.D	EN61000-4-2 INDUSTRY AIR : 8KV / Contact : 4KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
5	E.F.T	EN61000-4-4 INDUSTRY INPUT : 2KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
6	SURGE	IEC61000-4-5 INDUSTRY L-N : 2KV L,N-PE : 4KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
7	Test by certified Lab & Test Report Prepare				

## ■ RELIABILITY TEST

### ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT																																																																																																																																		
1	TEMPERATURE RISE TEST	MODEL : RSP-750-24 1. ROOM AMBIENT BURN-IN : 1.5 HRS I/P : 230VAC O/P : FULL LOAD Ta=33.6 °C 2. HIGH AMBIENT BURN-IN : 6 HRS I/P : 230VAC O/P : FULL LOAD Ta=48.2 °C			P																																																																																																																																		
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>PART NUMBER</th> <th>ROOM AMBIENT Ta=33.6 °C</th> <th>HIGH AMBIENT Ta=48.2 °C</th> </tr> </thead> <tbody> <tr><td>1</td><td>LF1</td><td>TR690-R1</td><td>42.1°C</td><td>58.2°C</td></tr> <tr><td>2</td><td>C2</td><td>105/275VAC 20% P=22.5 R46</td><td>41.7°C</td><td>57.5°C</td></tr> <tr><td>3</td><td>BD1</td><td>30A/800V SILICON US30KB80R</td><td>54.0°C</td><td>69.4°C</td></tr> <tr><td>4</td><td>L2</td><td>TF2432</td><td>48.4°C</td><td>64.1°C</td></tr> <tr><td>5</td><td>Q2</td><td>FCP22N60N 22A/600V</td><td>48.0°C</td><td>64.3°C</td></tr> <tr><td>6</td><td>C11</td><td>225/450V 10% P=22 MMX</td><td>40.0°C</td><td>56.9°C</td></tr> <tr><td>7</td><td>C5</td><td>330u/400V 105°C 30*30 HU</td><td>37.2°C</td><td>52.8°C</td></tr> <tr><td>8</td><td>T1</td><td>TF2419</td><td>44.6°C</td><td>58.9°C</td></tr> <tr><td>9</td><td>T2</td><td>TF2420</td><td>51.9°C</td><td>67.0°C</td></tr> <tr><td>10</td><td>Q901</td><td>STP7N95K3 7A/950V</td><td>47.4°C</td><td>62.2°C</td></tr> <tr><td>11</td><td>Q906</td><td>STP7N95K3 7A/950V</td><td>54.7°C</td><td>68.6°C</td></tr> <tr><td>12</td><td>Q100</td><td>V30100S 30A/100V</td><td>49.6°C</td><td>63.1°C</td></tr> <tr><td>13</td><td>Q200</td><td>V30100S 30A/100V</td><td>57.7°C</td><td>71.5°C</td></tr> <tr><td>14</td><td>D101</td><td>M6060C 60A/60V</td><td>58.2°C</td><td>72.3°C</td></tr> <tr><td>15</td><td>D900</td><td>BYV26EGP 1A/1KV DO-204AC</td><td>44.1°C</td><td>58.3°C</td></tr> <tr><td>16</td><td>D70</td><td>ST02D-170 AX078 T-52mm</td><td>46.3°C</td><td>61.5°C</td></tr> <tr><td>17</td><td>C75</td><td>220u/25V UL7Kh 8*11.5 KY</td><td>41.5°C</td><td>56.8°C</td></tr> <tr><td>18</td><td>T3</td><td>TF2431</td><td>43.1°C</td><td>58.0°C</td></tr> <tr><td>19</td><td>C320</td><td>100u/25V L5Kh 6.3*11 KY</td><td>43.3°C</td><td>58.2°C</td></tr> <tr><td>20</td><td>C301</td><td>1500u/16V UL10Kh 10*20 ZLH</td><td>42.1°C</td><td>57.0°C</td></tr> <tr><td>21</td><td>C161</td><td>470u/25V UL7Kh 8*20 KY</td><td>42.1°C</td><td>56.8°C</td></tr> <tr><td>22</td><td>L100</td><td>TF2428</td><td>51.2°C</td><td>66.0°C</td></tr> <tr><td>23</td><td>C110</td><td>1000u/35V UL10Kh 12.5*25 KY</td><td>47.1°C</td><td>61.7°C</td></tr> <tr><td>24</td><td>TSW1</td><td>BW-DCP-R0 80°C 105mm HH (H110)</td><td>41.4°C</td><td>57.2°C</td></tr> <tr><td>25</td><td>TSW2</td><td>BW-DCP-R0 85°C 60mm HH (H110)</td><td>53.3°C</td><td>67.4°C</td></tr> </tbody> </table>	NO	Position		PART NUMBER	ROOM AMBIENT Ta=33.6 °C	HIGH AMBIENT Ta=48.2 °C	1	LF1	TR690-R1	42.1°C	58.2°C	2	C2	105/275VAC 20% P=22.5 R46	41.7°C	57.5°C	3	BD1	30A/800V SILICON US30KB80R	54.0°C	69.4°C	4	L2	TF2432	48.4°C	64.1°C	5	Q2	FCP22N60N 22A/600V	48.0°C	64.3°C	6	C11	225/450V 10% P=22 MMX	40.0°C	56.9°C	7	C5	330u/400V 105°C 30*30 HU	37.2°C	52.8°C	8	T1	TF2419	44.6°C	58.9°C	9	T2	TF2420	51.9°C	67.0°C	10	Q901	STP7N95K3 7A/950V	47.4°C	62.2°C	11	Q906	STP7N95K3 7A/950V	54.7°C	68.6°C	12	Q100	V30100S 30A/100V	49.6°C	63.1°C	13	Q200	V30100S 30A/100V	57.7°C	71.5°C	14	D101	M6060C 60A/60V	58.2°C	72.3°C	15	D900	BYV26EGP 1A/1KV DO-204AC	44.1°C	58.3°C	16	D70	ST02D-170 AX078 T-52mm	46.3°C	61.5°C	17	C75	220u/25V UL7Kh 8*11.5 KY	41.5°C	56.8°C	18	T3	TF2431	43.1°C	58.0°C	19	C320	100u/25V L5Kh 6.3*11 KY	43.3°C	58.2°C	20	C301	1500u/16V UL10Kh 10*20 ZLH	42.1°C	57.0°C	21	C161	470u/25V UL7Kh 8*20 KY	42.1°C	56.8°C	22	L100	TF2428	51.2°C	66.0°C	23	C110	1000u/35V UL10Kh 12.5*25 KY	47.1°C	61.7°C	24	TSW1	BW-DCP-R0 80°C 105mm HH (H110)	41.4°C	57.2°C	25	TSW2	BW-DCP-R0 85°C 60mm HH (H110)	53.3°C	67.4°C		
NO	Position	PART NUMBER	ROOM AMBIENT Ta=33.6 °C	HIGH AMBIENT Ta=48.2 °C																																																																																																																																			
1	LF1	TR690-R1	42.1°C	58.2°C																																																																																																																																			
2	C2	105/275VAC 20% P=22.5 R46	41.7°C	57.5°C																																																																																																																																			
3	BD1	30A/800V SILICON US30KB80R	54.0°C	69.4°C																																																																																																																																			
4	L2	TF2432	48.4°C	64.1°C																																																																																																																																			
5	Q2	FCP22N60N 22A/600V	48.0°C	64.3°C																																																																																																																																			
6	C11	225/450V 10% P=22 MMX	40.0°C	56.9°C																																																																																																																																			
7	C5	330u/400V 105°C 30*30 HU	37.2°C	52.8°C																																																																																																																																			
8	T1	TF2419	44.6°C	58.9°C																																																																																																																																			
9	T2	TF2420	51.9°C	67.0°C																																																																																																																																			
10	Q901	STP7N95K3 7A/950V	47.4°C	62.2°C																																																																																																																																			
11	Q906	STP7N95K3 7A/950V	54.7°C	68.6°C																																																																																																																																			
12	Q100	V30100S 30A/100V	49.6°C	63.1°C																																																																																																																																			
13	Q200	V30100S 30A/100V	57.7°C	71.5°C																																																																																																																																			
14	D101	M6060C 60A/60V	58.2°C	72.3°C																																																																																																																																			
15	D900	BYV26EGP 1A/1KV DO-204AC	44.1°C	58.3°C																																																																																																																																			
16	D70	ST02D-170 AX078 T-52mm	46.3°C	61.5°C																																																																																																																																			
17	C75	220u/25V UL7Kh 8*11.5 KY	41.5°C	56.8°C																																																																																																																																			
18	T3	TF2431	43.1°C	58.0°C																																																																																																																																			
19	C320	100u/25V L5Kh 6.3*11 KY	43.3°C	58.2°C																																																																																																																																			
20	C301	1500u/16V UL10Kh 10*20 ZLH	42.1°C	57.0°C																																																																																																																																			
21	C161	470u/25V UL7Kh 8*20 KY	42.1°C	56.8°C																																																																																																																																			
22	L100	TF2428	51.2°C	66.0°C																																																																																																																																			
23	C110	1000u/35V UL10Kh 12.5*25 KY	47.1°C	61.7°C																																																																																																																																			
24	TSW1	BW-DCP-R0 80°C 105mm HH (H110)	41.4°C	57.2°C																																																																																																																																			
25	TSW2	BW-DCP-R0 85°C 60mm HH (H110)	53.3°C	67.4°C																																																																																																																																			
2	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR ( MIN )	I/P : 230 VAC O/P : 119 % LOAD Ta : 25°C	TEST : OK	P																																																																																																																																		
3	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P : 264VAC/100VAC O/P : 100 % LOAD Ta= -35 °C	TEST : OK	P																																																																																																																																		
4	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 50 °C NO DAMAGE	I/P : 272 VAC O/P : FULL LOAD Ta= 50 °C HUMIDITY= 95 %R.H	TEST : OK	P																																																																																																																																		
5	TEMPERATURE COEFFICIENT	± 0.03 %/°C (0~50°C)	I/P : 230 VAC O/P : FULL LOAD	± 0 %/°C (0~50°C)	P																																																																																																																																		

6	STORAGE TEMPERATURE TEST	<ol style="list-style-type: none"> <li>1. Thermal shock Temperature : -45°C ~ +90°C</li> <li>2. Temperature change rate : 25°C / MIN</li> <li>3. Dwell time low and high temperature : 30 MIN/EACH</li> <li>4. Total test cycle : 5 CYCLE</li> <li>5. Input/Output condition : STATIC</li> </ol>	OK	P
7	THERMAL SHOCK TEST	<ol style="list-style-type: none"> <li>1. Thermal shock Temperature : -35°C ~ +55°C</li> <li>2. Temperature change rate : 25°C / MIN</li> <li>3. Dwell time low and high temperature : 30 MIN/EACH</li> <li>4. Total test cycle : 10 CYCLE</li> <li>5. Input/Output condition : 230VAC/Full Load AC ON/OFF TEST turn on 58sec ; turn off 2sec</li> </ol>	OK	P
8	VIBRATION TEST	<p>1 Carton &amp; 1 Set</p> <ol style="list-style-type: none"> <li>(1) Waveform : Sine Wave</li> <li>(2) Frequency : 10~500Hz</li> <li>(3) Sweep Time : 12min/sweep cycle</li> <li>(4) Acceleration : 2G</li> <li>(5) Test Time : 60min in each axis (X.Y.Z)</li> <li>(6) Ta : 25°C</li> </ol>	TEST : OK	P
9	CAPACITOR LIFE CYCLE	<p>RSP-750-24:SUPPOSE C110 IS THE MOST CRITICAL COMPONENT</p> <ol style="list-style-type: none"> <li>(1) I/P : 230VAC O/P : FULL LOAD Ta= 25 °C LIFE TIME</li> <li>(2) I/P : 230VAC O/P : FULL LOAD Ta= 50 °C LIFE TIME</li> <li>(3) I/P : 230VAC O/P : 75% LOAD Ta= 50 °C LIFE TIME</li> <li>(4) I/P : 230VAC O/P : 50% LOAD Ta= 50 °C LIFE TIME</li> </ol>	<ol style="list-style-type: none"> <li>(1) 1205160HRS</li> <li>(2) 213000HRS</li> <li>(3) 277200HRS</li> <li>(4) 320640HRS</li> </ol>	P
10	MTBF	<p>Conducted by Parts Stress Analysis Prediction</p> <p>336.9K hrs min. Telcordia SR-332 ( Bellcore ) ; 109.1K hrs min. MIL-HDBK-217F (25°C)</p>		P
11	DMTBF/Accelerated Life Test	<p>Demonstration Mean Time Between Failure : Above 50,000 hours @ TA 50°C</p>		P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2012/5/16	RD SAMPLE	PASS	SANFORD SU	VINCENT TSENG
2012/7/11	PRODUCT SAMPLE	PASS	SANFORD SU	VINCENT TSENG
2012/8/7	PRODUCT SAMPLE W1207C22	PASS	SANFORD SU	VINCENT TSENG

2009/08/04 A50-F023